

Value+

Digital Multimeters

- Input Jack indicators;
- Display Backlight;
- Auto power off;
- Low battery indication;
- Auto range;
- k-type temperature measurement (MM62B);
- Non-contact Voltage Detection;
- Live wire checking;
- Installed with anti-burn fuse.



Digital Multimeters



Specifications

		MM62A	MM62B
DC Voltage	600mV/6V/60V/250V	±(0.8%+5)	±(0.8%+5)
AC Voltage	600mV/6V/60V/250V	±(1.5%+5)	±(1.5%+5)
DC Current	600μA/60mA/600mA/10A	±(1%+5)	±(1%+5)
AC Current	60mA/600mA/10A	±(1.5%+5)	±(1.5%+5)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+3)	±(0.8%+3)
Temperature	-20~400°C		±(3%+15)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±(1.5%+5)	±(1.5%+5)
Capacitance	6nF/60nF/600nF/6mF/60mF/600mF/6mF/60mF	±(4%+5)	±(4%+5)
Live		✓	✓
NCV		✓	✓
Auto Ranging		✓	✓
Diode		✓	✓
Continuity Buzzer		✓	✓
Data Hold		✓	✓
Low Battery Indication		✓	✓
Auto Power Off		✓	✓
Display Mode		Twisted Nematic	
Display Backlight		✓	✓
Flashlight		✓	✓
Max Display		5999	5999
Power By		1.5V AA x2	14500 Lithium Ion Rechargeable Battery
USB Charging			✓

*All information provided are subject to change without prior notice.

Your Distributor :



Futronix Co.

HONG KONG

www.futronix-hk.com

info@futronix-hk.com