

Wire Trackers

- No Calibration is needed for general measurement;
 - Allow User Calibration for precise measurement;
 - Able to measure cable made of different material;
 - Only need to connect the cable at one side;
 - Measure up to 400 meters;
 - Able to measure LAN cable (both 4P4C & 8P8C), Phone wire and BNC cable;
 - Intelligent wiremap Shorts, Split Pairs, and Breakpoint Checking);
 - Tracing cables connected to ethernet hub with PoE support;
 - Have Remote Identification Function (Optional);
 - Auto power off;
 - With display backlight and flashlight;
 - Sensitivity adjustable;
 - With Red Visible Laser (WT26F).






Specifications

| | | W126E | W126F | W126G | |
|--|---------------|--------------------------------|----------|----------|--|
| Cable Length Measurement | | | | | |
| 2-100m | Resolution | 0.1m | | | |
| | Best Accuracy | ±(1%+5m) | | | |
| 2-400m | Resolution | | 0.1m | 0.1m | |
| | Best Accuracy | | ±(1%+5m) | ±(1%+5m) | |
| Intelligent Wiremap | | | | | |
| Shorts | | ✓ | ✓ | ✓ | |
| Split pair | | ✓ | ✓ | ✓ | |
| Breakpoint checking | | ✓ | ✓ | ✓ | |
| Length of Network Cable | (8P8C) | ✓ | ✓ | ✓ | |
| Length of Network Cable | (4P4C) | ✓ | ✓ | ✓ | |
| Length of Phone Cable | | ✓ | ✓ | ✓ | |
| Length of BNC Cable | | ✓ | ✓ | ✓ | |
| Analogue Cable Tracing | | ✓ | ✓ | ✓ | |
| Digitalized Cable Tracing | | ✓ | ✓ | ✓ | |
| Port Blink Test | | ✓ | ✓ | ✓ | |
| Voltage Measurement (via network cable jack for reference) | | √ | √ | ✓ | |
| POE (Standard) Voltage Polarity
Checking | | | ✓ | ✓ | |
| POE (Non Standard) Voltage Polarity Checking | | ✓ | √ | ✓ | |
| POE (Standard) Voltage measure-
ment (for reference only) | | | ✓ | ✓ | |
| POE (Non-standard) Voltage mea-
surement (for reference only) | | ✓ | ✓ | ✓ | |
| Continuity (via network cable jack) | | ✓ | ✓ | ✓ | |
| Vibration inducation | | | | ✓ | |
| PoE Voltage Protection | | ✓ | ✓ | ✓ | |
| Remote Identification (Optional) | | 7 | 7 | 7 | |
| User Calibratable | | ✓ | ✓ | ✓ | |
| User Calibration Result Storage | | ✓ | ✓ | ✓ | |
| Red Visible Laser | | | ✓ | | |
| Max Display | | 9999 | 9999 | 9999 | |
| User Calibratable | | ✓ | ✓ | ✓ | |
| User Calibration Result Storage | | ✓ | ✓ | ✓ | |
| Display Backlight | | ✓ | ✓ | ✓ | |
| Flashlight | | ✓ | ✓ | ✓ | |
| Sensitivity adjustable | | ✓ | ✓ | ✓ | |
| Low power indication | | ✓ | ✓ | ✓ | |
| Auto power off | | ✓ | ✓ | ✓ | |
| Power By : Transmitter | | 3.7V 1360mAH Li-ion Battery x1 | | | |
| Receiver | | 9V 6F22 Battery x1 | | | |
| | | | | | |

Your Distributor:





WT26E / WT26G





Futronix Co. HONG KONG

www.futronix-hk.com info@futronix-hk.com